



COMMERCIAL 30 X-SERIES

UNMATCHED PERFORMANCE. MANEUVERABILITY. COMMERCIAL DURABILITY.

FEATURES

4.6-inch Deep Cutting Deck
3-in-1: Bag, Mulch or Side-Discharge

Commercial-Grade Engines
Kawasaki® or Kohler®

Blade Brake Clutch (BBC)
Allows the blade to be engaged and disengaged without stopping the engine

Patented Front Height Adjustment System
Eliminates the need for pivot-style adjusters



PRODUCTIVITY
Commercial 30 delivers the productivity of a larger walk-behind mower, with the versatility and maneuverability of a smaller machine. The 30-inch width of cut allows operators to cut 40 percent more with each pass than a 21-inch walk-behind mower.



COMMERCIAL DURABILITY
For increased durability in commercial use, the Commercial 30 comes standard with heavy-duty side braces, an engine guard, a metal side-discharge cover and a 1-inch diameter front bumper.

TOP ACCESSORIES

Micro-Mulch System

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

COMMERCIAL 30 X-SERIES

MODEL	ENGINE	SIZE	CONTROLS	WEIGHT	DIMENSIONS (W X H X L)
ECX180CKA30000	FJ180V Kawasaki KAI	30"	Self-propelled	185 lbs.	31.9" x 38.25" ¹ x 68.0" ¹
ECX200CKC30000	CV200 Kohler Command Pro	30"	Self-propelled	185 lbs.	31.9" x 38.25" ¹ x 68.0" ¹

¹ With handle in medium position. Varies with 0.5" cutting selections.



POWER COMPONENTS

Engine – CV200 Kohler engine; FJ180V Kawasaki KAI engine; governed to 3,500 rpm.

Air Filter – Quad-clean air cleaner

Drive System – Self-propelled, rear-wheel gear-driven.

Transmission – Infinitely variable speed selection.

Fuel Capacity – 1 gallon (3.8-L) fuel tank.

Speed – 0.0 mph to 3.8 (6.1 kmph) mph forward.

Speed Control - Finger-tip control.

DECK

Style – Fixed-deck. Ability to rear bag, side-discharge or mulch.

Widths Available – 30" (76 cm).

Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.5" (1.3 cm) increments.

Blade – 2 blades at 15.4".

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Engine Deck – 4.6-inch-deep stamped steel with welded reinforcement.

Front Tires – 9 x 2.5, semi-pneumatic.

Drive Tires – 10 x 3.0, semi-pneumatic.

Safety Package – Blade Brake Clutch (BBC).

Bag Capacity – 2.5 bushels (20 gallons).

ACCESSORIES & OPTIONS

Mulch Kit.

WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut ÷ 99 = acres per hour | 80% efficiency: MPH x width of cut ÷ 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® is a registered trademark of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.