



TURF TRACER® S-SERIES

QUALITY OF CUT. LONG-LASTING PERFORMANCE. ENHANCED CONTROL SYSTEM.

FEATURES

UltraCut™ Series 3 Deck
Side Discharge: 36 | 48 | 52

Commercial-Grade Engines
Kawasaki

Patented Enhanced Control System
Natural, ergonomic hand position helps reduce operator fatigue

Patented Belt Covers
Can be removed without tools for easy debris removal and quick belt access



LONG-LASTING PERFORMANCE
These hydro-drive models provide more control, instant response, and precise speed regulation with full-reverse and zero-turn maneuverability for unmatched productivity and durability.



CONVENIENT DECK LATCH
Changing the height of cut has been made easy with the added deck latch. Rather than holding the deck while changing the height of cut, the deck will now lock into place making it easier on operators. (Not available on 36-inch decks.)

TOP ACCESSORIES

- 3-Bushel Bagger
- Anti-Scalp Roller Kit
- Equipment Cover
- Micro-Mulch System
- Operator Controlled Discharge
- StandOn
- Turf Striping Kit

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

exmark.com

TURF TRACER S-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
TTS481CKA36300	FS481V Kawasaki V-Twin	36"	UltraCut Series 3	573 lbs.	47.5" x 42.0" x 77.7"
TTS481GKA48300	FS481V Kawasaki V-Twin	48"	UltraCut Series 3	586 lbs.	59.5" x 42.0" x 73.7"
TTS600GKA483E0	FS600V Kawasaki V-Twin Electric Start	48"	UltraCut Series 3	586 lbs.	59.5" x 42.0" x 73.7"
TTS600GKA523E0	FS600V Kawasaki V-Twin Electric Start	52"	UltraCut Series 3	670 lbs.	64.3" x 42.0" x 75.9"



POWER COMPONENTS

Engine – FS481V, FS541V, & FS600V Kawasaki V-Twin. All engines are governed to 3,600 rpm.

Air Filter – Standard Engine Manufacturer's air filter.

Drive System – Two Hydro-Gear® variable-displacement pumps and two high-efficiency Parker/Ross wheel-drive motors with 1" (2.54 cm) tapered shafts.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable selection from 0–6.2 mph (10.0 kmph) forward, 0–2.2 mph (3.5 kmph) reverse.

PTO Engagement – Magstop Electromechanical 105 ft-lb clutch.

Fuel Capacity – 5-gallon (18.9-L) fuel tank.

Drive-Wheel Release – Allows unit movement without engine running.

Deck Lift – Manual lift with hairpin from hole to hole for position adjustment.

DECK

Style – Full-floating UltraCut™ Series 3. Side discharge standard, with molded discharge chute and option to bag or mulch.

Deck Construction – 10-gauge top that is formed and continuously seam-welded, 7-gauge side skirt and 7-gauge welded spindle mounting locations for improved strength.

Widths Available – 36" (91.4 cm), 48" (121.9 cm) or 52" (132 cm).

Cutting Height – 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.

Blade Spindles – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 1.75"-diameter splined blade drive and 25mm (0.98") diameter spindle shaft.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Engine Deck – 7-gauge, heavy-duty welded steel.

Steering and Motion Control – Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.

Casters – .38" thick caster yoke arms.

Front Caster Tires – Double-yoke, 9 x 3.5–4, smooth tread, semipneumatic.

Drive Tires – 16 x 6.5–8, 4-ply Turf Master® on 36" models; 16 x 7.5–8, 4-ply Turf Master on all 48" and 52" models.

Tracking Adjustment – Insta-Track.

Turning Radius – True zero-turn.

Safety Package – Operator Presence Controls (OPC). Operator must have speed control lever in neutral and blades disengaged to leave operator's position without stopping engine.

Parking Brake – Lever-actuated mechanical compression.

Electrical – Electric start models – 12-volt battery and 15-amp alternator. Recoil start models – 5-amp clutch coil.

Standard Features – Engine hour meter.

ACCESSORIES & OPTIONS

3-Bushel Bagger, Anti-Scalp Roller Kit, Equipment Cover, Micro-Mulch System, Operator Controlled Discharge (Hand), StandOn, Turf Striping Kit and Weight Kit.

Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut ÷ 99 = acres per hour | 80% efficiency: MPH x width of cut ÷ 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Turf Tracer® are registered trademarks of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.