



TURF TRACER® X-SERIES

QUALITY OF CUT. LONG-LASTING PERFORMANCE. ENHANCED CONTROL SYSTEM.

FEATURES

UltraCut™ Series 3 Deck

Side Discharge: 52 | 60

Commercial-Grade Engines

Kohler

Patented Enhanced Control System

Natural, ergonomic hand position helps reduce operator fatigue

Patented Belt Covers

Can be removed without tools for easy debris removal and quick belt access



LONG-LASTING PERFORMANCE

These hydro-drive models provide more control, instant response, and precise speed regulation with full-reverse and zero-turn maneuverability for unmatched productivity and durability.



CONVENIENT DECK LATCH

Changing the height of cut has been made easy with the added deck latch. Rather than holding the deck while changing the height of cut, the deck will now lock into place making it easier on operators.

TOP ACCESSORIES

- 3-Bushel Bagger
- Anti-Scalp Roller Kit
- Equipment Cover
- Micro-Mulch System
- Operator Controlled Discharge
- StandOn
- Turf Striping Kit

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

exmark.com

TURF TRACER X-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
TTX650EKC52400	ECV650 Kohler EFI Electric Start	52"	UltraCut Series 4	720 lbs.	64.8" x 45.0" x 84.8"
TTX650EKC60400	ECV650 Kohler EFI Electric Start	60"	UltraCut Series 4	760 lbs.	73.0" x 45.0" x 84.8"
TTX650EKC604N0	ECV650 Kohler EFI Electric Start with StandOn and Mulch Kit	60"	UltraCut Series 4	840 lbs.	73.0" x 45.0" x 104.8"



POWER COMPONENTS

Engine – ECV650 Kohler EFI. All engines governed to 3,600 rpm.

Air Filter – Heavy-duty canister air filtration system.

Drive System – Two Hydro-Gear® variable-displacement pumps and two high-efficiency Parker/Ross wheel-drive motors with 1" (2.54 cm) tapered shafts.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable selection from 0–6.75 mph (10.9 kmph) forward, 0–2.25 mph (3.6 kmph) reverse.

PTO Engagement – MagStop Electromagnetic 200 ft-lbs clutch.

Fuel Capacity – 5-gallon (18.9-L) fuel tank.

Drive-Wheel Release – Allows unit movement without engine running.

Deck Lift – Manual lift with hairpin from hole to hole for position adjustment.

DECK

Style – Full-floating UltraCut™ Series 4. Side discharge standard, with molded discharge chute and option to bag or mulch.

Deck Construction – 10-gauge top that is formed and continuously seam-welded, 7-gauge side skirt and 7-gauge reinforcement rings at spindle assembly, 4-point suspension, full-floating deck with 6 adjustable anti-scalp rollers.

Widths Available – 52" (132 cm) or 60" (152.4 cm).

Cutting Height – 1.5" (3.8 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.

Blade Spindles – No maintenance, sealed and non-greasable spindles; 7.25"-diameter cutter housing with 1.75"-diameter splined blade drive and 25mm (0.98") diameter spindle shaft.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Engine Deck – 7-gauge, heavy-duty welded steel.

Steering and Motion Control – Hydro drive with Enhanced Control System (ECS), forward/reverse, left/right or zero-turn.

Casters – .38" thick caster yoke arms.

Front Caster Tires – Double-yoke, 11 x 4.0–5, smooth tread, semi-pneumatic.

Drive Tires – 18 x 8.5–8, 4-ply Turf Master.

Tracking Adjustment – Insta-Track.

Turning Radius – True zero-turn.

Safety Package – Operator Presence Controls (OPC). Operator must have speed control lever in neutral and blades disengaged to leave operator's position without stopping engine.

Parking Brake – Lever-actuated mechanical compression.

Electrical – 12-volt battery, 15-amp alternator, except for Kohler EFI has 20-amp alternator.

Standard Features – Enhanced engine hour meter.

ACCESSORIES & OPTIONS

3-Bushel Bagger, Anti-Scalp Roller Kit, Equipment Cover, Micro-Mulch System, Operator Controlled Discharge (Hand), StandOn and Turf Stripping Kit.

Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut = 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Turf Tracer® are registered trademarks of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.