



LAZER Z® E-SERIES 2025



4.26—5.32 Acres/Hour¹

Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping.



Up to 11 mph



9.5 Gallons



5-Year/1,250 Hours
Limited Warranty²



5+ Acre Property



Commercial

UltraCut™ Series 4 Decks

The full-floating deck uses maintenance free spindles with splined blade drivers to stop bolt tightening on impacts. The bearings on idler arm pivots are also maintenance free.

Less Time At The Pump

The Lazer Z E-Series features a single 9.5-gallon fuel tank with one fill location.

Fewer Grease Points

With just two grease points that only need annual greasing, the Lazer Z delivers maximum performance with minimum maintenance. Sealed spindles don't require greasing.

Tool-less Belt Removal

Deck and hydro belt can be installed without using any tools.

Unibody Frame

Our one-piece body frame is a classic case of "less is more." Because, fewer parts equal more strength and more durability. So, in the interest of accuracy, the Lazer Z's unibody frame is actually a case of "less is way more."

LAZER Z E-SERIES

	LRE730GKA48DA3	LRE730GKA524A3	LRE730GKA604A3	LRE801GKA524A3	LRE801GKA604A3	LRE810GBV604A3	LRE921GKA604A3
POWER COMPONENTS							
Engine	Kawasaki® FX730V V-Twin			Kawasaki FX801V V-Twin		Vanguard® 810cc	Kawasaki FX921V V-Twin
Air Filter	Heavy-duty						
Drive System	Dual Hydro-Gear® ZT-4400 w/ charge pumps, relief valves and independent, replaceable filters						
Forward Speed	11 mph						
PTO Engagement	MagStop Electromagnetic 175 ft-lb clutch with spot brake						MagStop Electromagnetic 200 ft-lb clutch with spot brake
Fuel Capacity	9.5-gallon single fuel tank						
DECK							
Size	48"	52"	60"	52"	60"		
Series	UltraCut Series 4						
Construction	10-gauge high-strength alloy top						
Lift	Foot-controlled						
Blade Quantity	2 blades						3 blades
Blade-Tip Speed	Approximately 18,500 fpm.						
Cutting Height	1.5" to 5.5" in 0.25"						
EQUIPMENT							
Caster Tires	13 x 6.5-6, smooth tread, pneumatic						
Drive Tires	24 x 9.5-12	24 x 9.5-12	24 x 12-12	24 x 9.5-12	24 x 12-12		
Steering Control	Hydraulically dampened twin levers						
Parking Brake	Lever-actuated internal wet disc brake						
Seat	Suspension seat with foam flip-up armrests						
Electrical	12-volt battery with 15-amp alternator						
Standard Features	Engine hour meter and cup holder						
Accessories	3-Bushel Bagger, 12V Adapter, 12V Power Port, Anti-Scalp Roller, Engine Maintenance Kit, Equipment Cover, Extended Drive Lever, Floor Mat, Full-Suspension Seat, Harness Add-On Accessory, Hitch, Hydro Maintenance Kit, Jack and Mount Receiver, LED Light, Micro-Mulch System, Operator Controlled Discharge, Seat Isolation System, Slope Sensor, Sunshade, Tractus Tire, Trash Container, Turf Striper, UltraVac Collection Systems and Custom Ride Seat Suspension <i>Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model</i>						
Warranty ²	Limited Warranty: 5-Year or 1,250 Hours (with No Hour Limit First 2 Years)						
WEIGHT AND MEASUREMENTS							
Width	61.2 in.	64.7 in.	72.7 in.	64.7 in.	72.7 in.	72.7 in.	72.7 in.
Length	87.8 in.	84.6 in.	84.6 in.	84.6 in.	84.6 in.	84.6 in.	84.6 in.
Height	70.1 in.	70.1 in.	70.1 in.	70.1 in.	70.1 in.	70.1 in.	70.1 in.
Weight	1,017 lbs.	1,019 lbs.	1,062 lbs.	1,037 lbs.	1,080 lbs.	1,006 lbs.	1,093 lbs.

EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • exmark.com



¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut ÷ 99 = acres per hour | 80% efficiency: MPH x width of cut ÷ 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Lazer Z® are registered trademarks of Exmark Mfg. Co., Inc. ©2025 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2025. Rev 1.