



LAZER Z® X-SERIES 2025



5.03—6.97 Acres/Hour¹

Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping.



Up to 11.5 mph



12 Gallons



5-Year/1,500 Hours
Limited Warranty²



5+ Acre Property



Commercial

UltraCut™ Series 6 Decks

Our full-floating side-discharge deck design uses dual-capture anti-scalp rollers and double-row sealed bearings for ultimate durability, with splined blade drivers to stop bolt tightening from impacts. Plus, our patented idler arm bearings are maintenance free. The new discharge chute improves clipping dispersal for the Exmark signature cut.

Maximum Productivity

With a combination of increased power, faster control response, larger cutting decks and a high-capacity hydro drive system, Lazer Z X-Series delivers maximum productivity.

Adapt Technology

Adjust deck rake quickly and easily to optimize cut quality and deck performance for a variety of turf types and conditions. Adapt is especially useful when mowing in wet, overgrown, or lush conditions, or stemmy grasses and weeds.

Increased Serviceability

The new Lazer Z X-Series is easier than ever to service, thanks to a rear engine guard that removes with just four bolts. Plus, a redesigned seat mount enables easier access to the engine and hydro drive components. Tools-free deck and hydro belt installation further eases maintenance.

Operator Comfort

Our new ergonomically-advanced operator seat features long-travel suspension and our exclusive iso-mount seat isolation. This seating system increases productivity by reducing operator fatigue, so each worker can work stronger, longer.

Vanguard Oil Guard System

Available on select models, the Oil Guard System increases mower uptime and decreases necessary in-season maintenance by extending oil change intervals to 500 hours, while also lowering engine oil temperature by 20-30 degrees.

LAZER Z X-SERIES

LRX801GKA526Q1 LRX801GKA606Q1 LRX820AKA606Q1 LRX820AKA726Q1 LRX921GKA606Q1 LRX921GKA726Q1 LRX993EBX606Q1 LRX993EBX726Q1 LRX980EKC606Q1 LRX980EKC726Q1

POWER COMPONENTS

Engine	Kawasaki® FX801V V-Twin		Kawasaki FX820V V-Twin		Kawasaki FX921V V-Twin		Vanguard® BIG BLOCK™ w/ Oil Guard System		Kohler® ECV980 Command Pro w/ ETB	
Air Filter	Heavy-duty									
Drive System	Two Exmark exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, shock valve, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components									
Forward Speed	10 mph				11.5 mph					
PTO Engagement	MagStop Electromagnetic 200 ft-lb clutch with spot brake				MagStop Electromagnetic 250 ft-lb clutch with spot brake					
Fuel Capacity	12-gallon single fuel tank									

DECK

Size	52"	60"	72"	60"	72"	60"	72"	60"	72"	
Series	UltraCut Series 6									
Construction	10-gauge top that is formed and continuously seam welded									
Lift	Foot-controlled and equipped with Adapt Technology									
Blade Quantity	3 blades									
Blade-Tip Speed	Approximately 18,500 fpm.									
Cutting Height	1.0" to 5.5" in 0.25"									

EQUIPMENT

Caster Tires	13 x 6.5-6, smooth tread, semi-pneumatic									
Drive Tires	23 x 9.5-12									24 x 12-12
Steering Control	Hydraulically dampened twin levers									
Parking Brake	Lever-actuated disc brake									
Seat	Deluxe adjustable suspension, 3" Travel with Seat Isolation System									
Electrical	12V battery w/ 15-amp alternator	12V battery w/ 30-amp alternator	12V battery w/ 15-amp alternator	12V battery with 30-amp alternator						
Standard Features	Engine hour meter, USB plug-in, phone tray and cup holder									
Accessories	3-Bushel Bagger, 12V Adapter, 12V Power Port, Anti-Scalp Roller, Engine Maintenance Kit, Equipment Cover, Extended Drive Lever, Floor Mat, Full-Suspension Seat, Harness Add-On Accessory, Hitch, Hydro Maintenance Kit, Jack and Mount Receiver, LED Light, Micro-Mulch System, Operator Controlled Discharge, Seat Isolation System, Slope Sensor, Sunshade, Tractus Tire, Trash Container, Turf Striper, UltraVac Collection Systems and Custom Ride Seat Suspension <small>Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model</small>									
Warranty ²	Limited Warranty: 5-Year or 1,500 Hours (with No Hour Limit First 2 Years)									

WEIGHT AND MEASUREMENTS

Width	64.8 in.	72.8 in.	72.8 in.	84.9 in.	72.8 in.	84.9 in.	72.8 in.	84.9 in.	72.8 in.	84.9 in.
Length	79.8 in.	83.4 in.	83.4 in.	86.1 in.	83.4 in.	86.1 in.	83.4 in.	86.1 in.	83.4 in.	86.1 in.
Height	70.5 in.	70.5 in.	70.5 in.	70.5 in.	70.5 in.	70.5 in.	70.5 in.	70.5 in.	70.5 in.	70.5 in.
Weight	1,200 lbs.	1,209 lbs.	1,256 lbs.	1,304 lbs.	1,256 lbs.	1,304 lbs.	1,256 lbs.	1,304 lbs.	1,256 lbs.	1,304 lbs.

EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • exmark.com



¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut ÷ 99 = acres per hour | 80% efficiency: MPH x width of cut ÷ 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Lazer Z® are registered trademarks of Exmark Mfg. Co., Inc. ©2025 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2025. Rev 2.