



TORO® DINGO® TX 525

COMPACT UTILITY LOADERS

The original tracked compact utility loaders, Toro Dingo TX 525 models deliver durability and reliability pros and do-it-yourselfers trust, combined with powerful performance and incredible versatility. For operators who are frequently switching tasks or moving things out of the way, these walk-behind models provide greater productivity due to the ability to walk up to the machine and go. In addition, with walk-behind Dingos, operators don't feel the bumps when going over rough terrain.

FEATURES



LOW-IMPACT FOOTPRINT

Long-lasting, Kevlar® reinforced tracks disperse weight evenly for a light footprint on turf, while delivering better traction in sandy or wet ground conditions.

HIGH-PERFORMANCE HYDRAULICS

The 4-pump hydraulic system directs power right where you need it. Operate the loader, bucket, traction and auxiliary drives at the same time for increased operator efficiency.

EXCLUSIVE TX CONTROLS

Three simple controls let operators get to work fast:

- 1** Curl, dump or float the bucket while raising or lowering the loader arms with one hand using the joystick.
- 2** Grab the one-handed traction drive from any angle for effortless control.
- 3** Activate the auxiliary circuit control lever to power the attachments instantly.



TORO® DINGO® TX 525

SPECIFICATIONS

		TX 525 NARROW TRACK (MODEL 22323)	TX 525 WIDE TRACK (MODEL 22324)
ENGINE	Engine	Kubota® D902 diesel 24.8 HP* (18.5kw)	
	Air Filter	Two-stage, heavy-duty, remote	
	Cooling System	Liquid Cooled	
	Fuel Tank	6.0 gallons (23 liters)	
	Oil Capacity	3.84 quarts (3.63 liters)	
HYDRAULIC SYSTEM	Hydraulic Pressure	3,000 PSI (20,684 kPa)	
	Hydraulic Flow	Traction: 16.9 gpm (each pump) Auxiliary: 13.8 gpm	
	Reservoir Capacity	10 gallons (37.8 liters)	
TRACKS	Standard	Sprocket-drive, 10 road wheels per side	
	Traction	Dual hydrostatic pump	
DIMENSIONS	Track Dimensions	96.6" x 5.9" (245.3 cm x 14.9 cm)	96.6" x 9.5" (245.3 cm x 24.1 cm)
	Wheelbase	31.2" (79.2 cm)	
	Ground Clearance	4.6" (11.6 cm)	
	Overall Dimensions (WxLxH) With Bucket	33.7" x 92" x 46.1" (86.5 x 233.6 x 117.0 cm)	41" x 92" x 46.1" (104.1 x 233.6 x 117.0 cm cm)
	Overall Dimensions (WxLxH) Without Bucket	33.7" x 70.7" x 46.1" (86.5 x 179.5 x 117.0 cm)	41" x 70.7" x 46.1" (104.1 x 179.5 x 117.0 cm cm)
	Maximum Operating Height	90.1" (228.8 cm)	
	Hinge Pin Height	65.8" (167.1 cm)	
	Dump Height	46.1" (117.0 cm)	
	Dump Angle	38-degrees	
	Reach - Fully Raised	21.8" (55.3 cm)	
	Ground Speed	Fwd: 0–4.5 mph (0–7.2 km/h) Rev: 0–2.0 mph (0–3.2 km/h)	
	Weight	1,904 lbs (863.6 kg)	2,013 lbs (913.0 kg)
Tip Capacity	1,580 lbs. (716.6 kg)	1,530 lbs. (693.9 kg)	
Rated Operating Capacity (35% of Tip Capacity)*	553 lbs. (250.8 kg)		
Ground Pressure	5.2 PSI	3.4 PSI	

*Per ISO 14397-1

©2023 The Toro Company

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligation. See your dealer for details on all of our warranties. toro.com/dingo



Count on it.