AB80J/AB85J

ARTICULATED BOOM LIFTS



- The ultimate diesel articulated booms
- Excellent aerial maneuverability with "up & over" capabilities
- Powerful 4 wheel drive and 4 wheel steer
- Smooth, precise, easy to use controls
- Simple to maintain and service



ARTICULATED BOOM LIFTS


DIMENSIONS	AB80J	AB85J
Max. working height	85 ft 11 in	90 ft 6 in
Max. platform height	79 ft 11 in	84 ft 6 in
Max. horizontal reach	59 ft 5 in	61 ft 11 in
Clearance height at max. outreach	27 ft 11 in	27 ft 11 in
Platform size	8 ft x 3 ft	8 ft x 3 ft
Overall width (A)	8 ft 6 in	8 ft 6 in
Overall length (B)	32 ft 2 in	41 ft 2 in
Stowed height (C)	9 ft 10 in	9 ft 10 in
Ground clearance	13 in	13 in

PERFORMANCE			
Platform capacity (SWL)	500 lbs	500 lbs	
Max. wind speed	28 mph	28 mph	
Max. drive height	79 ft 11 in	84 ft 6 in	
Max. drive speed (stowed)	3.0 mph	3.0 mph	
Max. drive speed (elevated)	0.6 mph	0.6 mph	
Jib length	5 ft	6 ft 6 in	
Jib arc	140°	135°	
Jib rotation	n/a	140° side to side	
Platform rotation	150°	150°	
Superstructure rotation (continuo	ous) 360°	360°	
Tailswing	35 in	35 in	
Raise/lower time	240/240 seconds	240/240 seconds	
Gradeability	30%	30%	
Inside turning radius	7 ft 10 in	7 ft 10 in	
Outside turning radius	15 ft 5 in	15 ft 5 in	
Tires	15 x 625 foam filled lug		
Controls	proportional joystick		
Drive system	4 wheel drive		


POWER	
Power source	Kuhota V2403 65hn digsal - Tigr 4 Final

WEIGHT		
Weight	36,800 lbs	38,580 lbs

WORKING ENVELOPE



AB80J/AB85J



STANDARD FEATURES

- Snorkel Guard™ secondary guarding system
- Hydraulic platform rotation
- Four wheel drive, steer and crab steer
- Foam filled lug tires
- 360° continuous turntable rotation
- Proportional drive, lift & swing, extend & rotate
- Drive motion alarm
- Flashing amber light
- Horn
- Dual lanyard attachment points
- Power line to platform
- 5° tilt alarm
- 2 year parts & labor, 5 year structural warranty
- ANSI compliant

OPTIONS

- Special paint colors
- Airline to platform
- Non-marking tires
- AC generator 110V/240V 2kW
- Aircraft package
- Deluxe aircraft package
- Cold weather package
- Extreme cold weather package
- Extreme environment package
- Light package
- Tow kit
- Glazier package
- Utility package
- 12kW generator package
- 12kW generator/welder package
- Dual fuel
- Environmental hydraulic oil
- Tool tray

Ssnorkel

P.O. Box 1160

St.Joseph, MO 64502-1160, USA

Tel: 1 (785) 989-3000

Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070

Email: sales.usa@snorkellifts.com