## TM12E/TM16E ELECTRIC DRIVE TELESCOPIC MAST LIFTS



- Industry-leading electric drive telescopic mast lifts
- Versatile, robust and simple to use
- Drives through a standard doorway
- Smooth & efficient electric drive
- Ideal for many applications from construction to stockpicking



### **ELECTRIC DRIVE TELESCOPIC MAST LIFTS**


DIMENSIONS	TM12E	TM16E
Max. working height	18 ft	22 ft
Max. platform height ( <b>A</b> )	12 ft	16 ft
Platform size (stowed)	27 in x 39 in	27 in x 39 in
Platform size (extended) ( <b>E</b> )	27 in x 59 in	27 in x 59 in
Extension deck length	20 in	20 in
Overall length ( <b>D</b> )	4 ft 6 in	4 ft 6 in
Overall width ( <b>B</b> )	2 ft 6 in	2 ft 6 in
Stowed height (C)	5 ft 6 in	6 ft 6 in
Ground clearance	3 in	3 in

PERFORMANCE		
Platform capacity (SWL)	500 lbs	500 lbs
Max. drive height	12 ft	16 ft
Max. wind speed	28 mph	0 mph
Max. drive speed (stowed)	2.5 mph	2.5 mph
Max. drive speed (elevated)	0.4 mph	0.4 mph
Raise/lower time	12.5/10.5 sec	12.5/10.5 sec
Gradeability	25%	25%
Max. operating slope (side to side)	2°	1.5°
Max. operating slope (front to back)	2°	1.5°
Inside turning radius	0 in	0 in
Outside turning radius	55.5 in	55.5 in
Tires	12.7 in non-marking rubber	
Parking brake	2 wheel, spring-applied, electric release	
Drive system	dual DC motors	
Controls	proportional	

POWER

Power source	24V 220 Ah I	24V 220 Ah batteries		
Battery charger	20 Am	20 Amp		
WEIGHT				
Weight	1,850 lbs	2,430 lbs		


**TURNING RADIUS** 



ANSI Specification ©Snorkel 2020

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance \* Preliminary specifications - confirm at time of ordering.

# TM12E/TM16E



### **STANDARD FEATURES**

- Roll-out deck extension •
- Proportional controls •
- Saloon-door style entry gates •
- Descent & tilt alarms •
- Emergency lowering at chassis controls •
- Non-marking rubber tires •
- 2 persons indoor •
- 1 person outdoor (TM12E) .
- Crane lift points
- Hour meter & on-board diagnostics display •
- Horn
- Selectable motion alarm •
- Integrated battery charger, 110V 20A •
- 2 year parts & labor, 5 year structural warranty •
  - ANSI compliant

#### **OPTIONS**

•

- Special paint colors
- Environmental hydraulic oil •
- Order picker tray (TM12E only) •



P.O. Box 1160 St.Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070 Email: sales.usa@snorkellifts.com

02/2020

.com