



SnowDogg® MD75II Snow Plow

Buyers Part Number: MD75II

Full-size power and features in a package optimized for 1/2 ton trucks like the Ford® F-150, Chevy® Silverado 1500, and RAM® 1500

- Redefine what your 1/2 ton truck can do.
- The corrosion resistant 304 stainless steel moldboard never needs paint. A robust frame spreads impact across the blade to reduce wear on vital components. • Full-length 1-3/8 in. cross tube • Six 3/16 in. laser-cut steel ribs • 3/8 in. steel cutting edge
- SnowDogg Illuminator™ LED Headlights are brighter and longer lasting than traditional halogens. Active Defrosting Technology™ keeps the Illuminators ice-free even in the biting cold - a central heat source defrosts the entire lens evenly, preventing the streaking or banding that's common with other LED plow lights. SnowDogg HX High Intensity Halogens are also available.
- The tubular steel Floating A-Frame features a sliding-pin connection so the plow contours the ground for a clean, efficient scrape. Outstanding performance at any mounting height.
- Mount and dismount in record time with the new RapidLink™ Attachment System. • Center-mounted drop foot props up your plow with the pull of a handle • Hydraulically powered Jack Switch™ adjusts your plow's mounting height on the fly so it's easy to line up with your vehicle • Connects to your truck with a single driver's side foot pedal • Works with all existing SnowDogg MD / VMD truck mounts.
- Two stress-optimized trip springs protect your equipment from hidden curbs and obstacles.
- From the municipal style chain lift to the fully enclosed hydraulic power unit, the MDII handles whatever winter throws at you. • 1/4 in. grade 50 steel construction • Powerful lift cylinders • Over-sized 1-1/2 in. angle cylinders • Fully enclosed 2 HP hydraulic power unit • SAE standard cartridge valves and hefty 3/8 in. rubber hoses • Optimized hose routing
- Intuitive in-cab controls are simple to use even with gloves on. The backlit one-handed controller puts all plows functions in the palm of your hand. Other standard accessories: • Contoured poly snow deflector • Cast shoes • Wire reinforced blade guides



Specifications

Specifications continued:

Angle Cylinders	1 1/2 x 10"	Angled Blade Width	78.0"
Blade Height	24"	Blade Width	90"
Cutting Edge	3/8 x 6"	Electrical	Headlamp Rated Replaceable Micro-ISO Relays
Harnesses	Separate Light and Hydraulic 4GA Power Wires	Lift Cylinder	1 1/2 x 6"
Lights	Dual Halogen Bulbs or Illuminator™ Heated LEDs	Moldboard Material	304 Stainless Steel
Moldboard Thickness	14 Ga	Mounting System	RapidLink™
Plow Shoes	Standard	Plow Type	Straight Blade
Ribs	8	Snow Deflector	Contoured Poly
Stand	Drop Foot	Trip Springs	2
Trip Style	Full Trip	Shipping Weight	400 lb