



SnowDogg® TE75II Snow Plow with RapidLink™ Attachment System

Buyers Part Number: TE75IIR

Buyers Products SnowDogg TEII Snow Plow combines the rugged, reliable strength of the flagship EX Series with a versatile trip edge design.

- The corrosion resistant 304 stainless steel moldboard never needs paint. A robust frame spreads impact across the blade to reduce wear on vital components. • Full-length 2 in. cross tube • Eight 1/4 in. laser-cut steel ribs • 1/2 in. cutting edge
- SnowDogg Illuminator™ LED Headlights are brighter and longer lasting than traditional halogens. Active Defrosting Technology™ keeps the Illuminators ice-free even in the biting cold - a central heat source defrosts the entire lens evenly, preventing the streaking or banding that's common with other LED plow lights. SnowDogg HX High Intensity Halogens are also available.
- Mount and dismount in one minute or less with the new RapidLink™ Attachment System. • Center-mounted drop foot props up your plow on any surface with the pull of a handle • Hydraulically powered Jack Switch™ adjusts your plow's mounting height on the fly so it's easy to line up with your vehicle • Connects to your truck with a single driver side foot pedal
- The tubular steel Floating A-Frame features a sliding-pin connection so the plow contours the ground for a clean, efficient scrape. Outstanding performance at any mounting height.
- The moldboard has a 6 in. trip edge with two pairs of stress-optimized trip springs. The design helps you plow over hidden obstacles and uneven terrain without losing your load or damaging your truck or equipment.
- From the municipal style chain lift to the fully enclosed hydraulic power unit, SnowDogg plows are built to endure whatever winter throws at you. • Powerful 2 in. lift cylinder • Over-sized 1-1/2 in. angle cylinders • Fully enclosed 2 HP hydraulic power unit • SAE standard cartridge valves and hefty 3/8 in. rubber hoses • Central hydraulic-operated life frame available
- Intuitive in-cab controls are simple to use even with gloves on. The backlit, one-handed controller puts all plows functions in the palm of your hand. Other standard accessories: • Contoured poly snow deflector • Cast shoes • Wire reinforced blade guides



Specifications

Specifications continued:

Angle Cylinders	1 1/2 x 12"	Angled Blade Width	78.0"
Blade Height	31"	Blade Width	90"
Cutting Edge	1/2 x 6"	Electrical	Headlamp Rated Replaceable Micro-ISO Relays
Harnesses	Separate Light and Hydraulic 4GA Power Wires	Lift Cylinder	2 x 6"
Lights	Dual Halogen Bulbs or Illuminator™ Heated LEDs	Moldboard Material	304 Stainless Steel
Moldboard Thickness	12 Ga	Mounting System	RapidLink™ Attachment System
Plow Shoes	Standard	Plow Type	Straight Blade
Ribs	8	Snow Deflector	Contoured Poly
Stand	Drop Leg	Trip Springs	4
Trip Style	Trip Edge	Shipping Weight	705 lb