

## SnowDogg® VXF85II Snow Plow with RapidLink™ Attachment System

**Buyers Part Number: VXF85IIR** 

Buyers Products SnowDogg VXFII Snow Plow gives commercial users a powerful and versatile v-blade with intuitive one-handed controls.

Dual corrosion resistant 304 stainless steel moldboards never need paint. A robust frame spreads impact across the blades to reduce wear on vital components.
 Full-length 2 in. cross tube
 Heavy duty bottom channel
 Four 1/4 in. lasercut steel ribs per wing
 1/2 in. cutting edges



- Mount and dismount in one minute or less with the new RapidLink™ Attachment System.
  Center-mounted drop foot props up your plow on any surface with the pull of a handle •
  Hydraulically powered Jack Switch™ adjusts your plow's mounting height on the fly so it's easy to line up with your vehicle Connects to your truck with a single driver side foot pedal
- The tubular steel Floating A-Frame features a sliding-pin connection so the plow contours the ground for a clean, efficient scrape. Outstanding performance at any mounting height.
- From the municipal style chain lift to the fully enclosed hydraulic power unit, the VXFII is built to endure whatever winter throws at you. Powerful 2 in. lift cylinders Over-sized 1-1/2 in. angle cylinders Fully enclosed 2 HP hydraulic power unit SAE standard cartridge valves and hefty 3/8 in. rubber hoses
- Double acting 1-3/4 in. angle cylinders make it easy to put snow where you want it. Back drag with confidence, even in tight spaces.
- Each wing has an independent 6 in. trip edge and two stress-optimized trip springs to protect your equipment from hidden curbs and obstacles without dumping the snow you're pushing.
- Intuitive in-cab controls are simple to use even with gloves on. The backlit, one-handed controller puts all plows functions, including angle, scoop, and V, in the palm of your hand.
   Other standard accessories: • Contoured poly snow deflector • Wire reinforced blade guides

## **Specifications**

## **Specifications continued:**

Angle Cylinders	1 1/2 x 1 3/4 x 12"	Angled Blade Width	88.0"
Blade Height	29/37"	Blade Width	102"
Cutting Edge	1/2 x 6"	Electrical	Headlamp Rated Replaceable Micro-ISO Relays
Harnesses	Separate Light and Hydraulic 4GA Power Wires	Lift Cylinder	2 x 6"
Lights	Dual Halogen Bulbs or Illuminator™ Heated LEDs	Moldboard Material	304 Stainless Steel
Moldboard Thickness	12 Ga	Mounting System	RapidLink™ Attachment System
Plow Shoes	Optional	Plow Type	V Plow
Ribs	6	Snow Deflector	Contoured Poly
Stand	Drop Leg	Trip Springs	4
Trip Style	Trip Edge	Shipping Weight	978 lb