



# TORO® DINGO® TXL 2000

COMPACT UTILITY LOADERS



## OUTSTANDING REACH & LIFT HEIGHT

Thanks to the telescoping loader arm technology, operators are able to backfill behind a retaining wall, dump material into the center of a full-size dump truck or dumpster and offload both rows of a trailer from one side with ease.

HINGE PIN HEIGHT  
OF JUST OVER  
**10 FT**



## OUTSTANDING VISIBILITY

With a stand-on operator platform instead of a cab, the TXL 2000 provides 360° visibility. No need for a back-up camera — just turn and look.



## OUTSTANDING CAPACITY

With up to 2,000 lbs (907 kg) of operating capacity, the TXL 2000 has the muscle for demanding jobs.



## EASE OF USE

TXL 2000 control interface is easy to use and master — no special equipment licensing required.

## OTHER FEATURES & BENEFITS

- Kubota D1803 49.6 hp Tier 4 Final with DOC (diesel oxidation catalyst) minimizes downtime with no regeneration required.
- Smart Power technology automatically adjusts traction speed to maximize engine, auxiliary, and traction torque for greater operation efficiency - a selectable option through the info center.
- Selectable traction speed allows operators to customize machine speed based on operator preference and project application.
- Proportional auxiliary control allows the operator to run attachments at their desired speed.



## OUTSTANDING ACCESS

Easy for operators of different sizes to jump on and off the machine instead of getting into and out of a cab.



## OUTSTANDING MANEUVERABILITY

Maneuver in and out of small spaces where other machines just can't go.





# TORO® DINGO® TXL 2000

## SPECIFICATIONS

		DINGO TXL 2000 WITH TELESCOPING ARMS (MODEL 22530)	DINGO TXL 2000 WITHOUT TELESCOPING ARMS (MODEL 22531)
<b>ENGINE</b>	Engine	49.6 hp (37 kW) Kubota D1803 Diesel	
	Air Filter	Two-stage, heavy-duty, remote	
	Cooling System	Liquid Cooled	
	Fuel Tank	18.3 gallons (69.3 liters)	
	Oil Capacity	7.4 quarts (7 liters)	
<b>HYDRAULIC SYSTEM</b>	Hydraulic Pressure	Auxiliary: 3,000 PSI Traction: 4,350 PSI	
	Hydraulic Flow	Auxiliary: 21.4 gpm Traction: 21.5 gpm (81.4 lpm) each pump	
	Reservoir Capacity	15.25 gallons (57.7 liters)	
<b>TRACKS</b>	Standard	Sprocket-drive, 6 road wheels per side	
	Traction	Dual hydrostatic pump	
<b>DIMENSIONS</b>	Track Dimensions	162.2" x 11.8" (411.9 cm x 29.9 cm)	
	Wheelbase	53.7" (136.4 cm)	
	Ground Clearance	6.3" (16.0 cm)	
	Overall Dimensions (WxLxH) With Bucket	55" x 136.9" x 67.8" (139.7 x 347.7 x 172.2 cm)	
	Overall Dimensions (WxLxH) Without Bucket	55" x 98.8" x 67.8" (139.7 x 250.9 x 172.2 cm)	
	Maximum Operating Height	Telescoping 67.8" (172cm)	Non-Telescoping 63.9" (162 cm)
	Hinge Pin Height	123.4" (313.4 cm)	98.6" (250.4 cm)
	Dump Height	88.9" (225.8 cm)	64.1" (162.8 cm)
	Dump Angle	46.3-degrees	
	Reach - Fully Raised	45.2" (114.8 cm)	26.1" (66.2 cm)
Ground Speed	5.4 mph (8.6 km/h)		
Weight	6,690 lbs (3,034.5 kg)		
Tip Capacity	5,715 lbs (2,592.2 kg) retr, 2,620 lbs (1,188.4 kg) ext.	5,715 lbs (2,592.2 kg)	
Rated Operating Capacity (35% of Tip Capacity)*	2,000 lbs (907.1 kg) retr, 920 lbs (417.3 kg) ext.	2,000 lbs (907.1 kg)	
Ground Pressure	5.3 PSI		

\*Per ISO 14397-1

