



Skid Steer Snow Pusher - 8 Foot

Buyers Part Number: 2603108

Combines the unyielding efficiency of a large containment plow with the maneuverability of a skid steer.

- Universal quick coupler works with any skid steer.
- Strong, reliable construction features dual 4 in. channels.
- Abrasion-resistant wear shoes made of AR400 steel.
- Durable 7 Ga rolled steel moldboard.
- Premium grade rubber compound cutting edge.
- Durable Tuff-Kote™ powder coat protects your pusher for years to come.
- Pull snow away from buildings, docks, and other tight places with the optional back drag kit.
- Included high-visibility blade guides.



Specifications

Carriage Bolt Size	.625 - 11	Carriage Bolt Grade	5
Cutting Edge Dimensions	1.0 x 6.0"	Cutting Edge Material	High Tensile Strength Rubber
Depth (front of shoe to back of pusher)	37"	Finish	Powder Coat with Primer
For Use With (Equipment Type)	Skid-Steer	Friction Surface Thickness	0.75"
Friction Surface Width	5"	Height (bottom of shoe to top of side plate)	39"
Included Reflective Decals	Yes	Minimum Required Horsepower	46 HP

Specifications continued:

Minimum Required Machine Weight	5500 lb	Moldboard Gauge	7 Ga
Moldboard Material	Carbon Steel	Shoe Material	AR400 Steel
Side Plate Support Dimensions	3.00 x 3.00 x .250"	Side Plate Thickness	0.313"
Trip Protection	None	Width	8'
Shipping Weight	775 lb		