

EV Crew

LITHIUM- ION BATTERY

UP TO 65 MILES

65 MILE RANGE* | 24 MPH MAX SPEED | RAPID CHARGE TECHNOLOGY | ULTRA SMOOTH RIDE (L-ROSS)

(vehicle shown with optional accessories)



DUAL POWER

SWITCH

ROLLOVER PROTECTION STRUCTURE CERTIFIED

HOUR METER STANDARD



60 to 70 mile range is with the optional extended battery kit. Standard mileage is 45 mile while driving in max-distance mode at 65° or warmer. Image shown with optional accessories

	SIANDARD FEATURES
BATTERY	51V 250AH Lithium-Ion (Life P04) Battery Pack
DRIVE TRAIN	2WD
SPEED	24mph
CHARGE TIME	2.5 Hours for Rapid Charge / 8 Hours for Full Charge
RANGE	55 Miles With Our 160AH Life P04 Extended-Range Battery
SAFE RETURN HOME	Audible and visual warning at 10% state of charge
L-ROSS COMFORT	LROSS (Landmaster Ride Optimization Suspension System) provides an ultra-smooth riding experience over ridges, rocks, logs, and other rough terrain.





EV Crew



/		
/	POWER	AC motor, powered by a 48V DC L 16 HP for short term peak with 160
/	SEATING CAPACITY	4-Person*
/	SPEED	24MPH (Programmed at factory for LSV ar
,	FUEL CONSUMPTION	NA
/	RANGE	Up to 55 miles (in MAX DISTANCE mode v
/	STARTING	Keyed on/off
/	BATTERY	51V 160AH Lithium-Ion
/	SPARK PLUG	N/A
/	CHARGE	2.5hrs rapid charge / 8hrs full char
/	ALTERNATOR	Converter / 30 amps
/	TRANSMISSION	Direct drive
(TRANSAXLE	H-12 Schafer / DANA oil filled gear
/	DIFFERENTIAL	Limited Slip Differential
/	DRIVE	2 wheel drive
/	FRONT SUSPENSION	Double A-arms, adjustable coil ove
/	REAR SUSPENSION	Independent trailing arm, with dua
/	BRAKE SYSTEM	4 wheel disc, hydraulic brake
/	TIRES	25" DOT On Road / Off Road Tire
/	DIMENSIONS	127" L x 59" W x 76" H
(WHEEL BASE	105"
	TURNING RADIUS	16' inside radius
	GVRW	2412 lbs. / 2612 lbs. with HD LROS
	CURB WEIGHT	1412 lbs. with 160 AH battery
	BED MATERIALS	Structural foam "Poly Bed" with sta
	BED DIMENSIONS	35.25" L x 41.5" W x 11" D
	BED CAPACITY	9.25 cu.ft. / 500 lbs. standard LRO
	TOWING CAPACITY	1200 lbs.
	TOTAL PAYLOAD	1000 lbs. / 10000 lbs.
	WARRANTY	2 year motor / all other 1 year limit
		On-board charger, 3pt lap/ shoulder be

ADI

THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The Easy Life Warranty from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. As long as you care for your machine like you should, don't wreck it, or crush it, or let it be attacked by unruly farm animals, we're going to cover it. Except for tires, brake pads, batteries, damage, neglect. That's /the limit. Visit AmericanLandMaster.com to learn more.

Lithium-Ion Battery at 12K Watts with 600 amp Navitas controller (6.7 HP for long term driving, 0 Amp Hour Battery)

ATING CAPACITY	4-Person*	
EED	24MPH (Programmed at factory for LSV and Flip Seat compliance. Max speed of 30 available with Blue Tooth app.)	/
EL CONSUMPTION	NA	
NGE	Up to 55 miles (in MAX DISTANCE mode with 160 AH battery @ 65 Degrees)**	
ARTING	Keyed on/off	/
TTERY	51V 160AH Lithium-Ion	
ARK PLUG	N/A	
IARGE	2.5hrs rapid charge / 8hrs full charge	/
TERNATOR	Converter / 30 amps	
ANSMISSION	Direct drive	/
ANSAXLE	H-12 Schafer / DANA oil filled gearbox	1
FERENTIAL	Limited Slip Differential	
IVE	2 wheel drive	/
ONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 8" travel	
AR SUSPENSION	Independent trailing arm, with dual-rate coil over shock with up to 8" of travel	
AKE SYSTEM	4 wheel disc, hydraulic brake	/
RES	25" DOT On Road / Off Road Tire (8" front 10" back)	
MENSIONS	127" L x 59" W x 76" H	/
HEEL BASE	105"	/
RNING RADIUS	16' inside radius	
/RW	2412 lbs. / 2612 lbs. with HD LROSS	/
	1412 lbs. with 160 AH battery	
D MATERIALS	Structural foam "Poly Bed" with stake pockets	ļ
D DIMENSIONS	35.25" L x 41.5" W x 11" D	/
D CAPACITY	9.25 cu.ft. / 500 lbs. standard LROSS suspension / 700 lbs. HD LROSS suspsension	
WING CAPACITY	1200 lbs.	/
TAL PAYLOAD	1000 lbs. / 10000 lbs.	/
ARRANTY	2 year motor / all other 1 year limited, 5 year prorated Lithium battery	
DITIONAL FEATURES	On-board charger, 3pt lap/ shoulder belts for driver & passenger, 12V/18W LED headlights, 2" rear and front receiver hitch, welded steel/frame, Single 12V auxiliary outlet, polyurethane powder paint. Electronic power steering. Weather-sealed wiring connections. In-dash, hour meter. LED charge meter for the 48 volt system. Low charge audible warning. Battery shut down switch. Wide slection of additional accessories available along with three bed options.	/

* 2 additional seats with optional seat bed. ** Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.