

## 65 MILE RANGE\* | RAPID CHARGE TECHNOLOGY | ULTRA SMOOTH RIDE (L-ROSS)

(vehicle shown with optional accessories)



60 mile range is with the optional extended battery kit. Standard mileage is 45 mile while driving in max-distance mode at 65° or warmer. Image shown with optional accessories.

STANDARD FEATURES	
DRIVE TRAIN	2WD
SPEED	24MPH (Programmed at factory for LSV and Flip Seat compliance. Max speed of 30 available with Blue Tooth app.)
CHARGE TIME	5 hours for the Standard Battery / 8 Hours for the Extended-Range Battery
RANGE	45 Miles With Standard Battery / 65 Miles With Extended-Range Battery
SAFE RETURN HOME	Audible and visual warning at 10% state of charge
L-ROSS COMFORT	LROSS (Landmaster Ride Optimization Suspension System) provides an ultra-smooth riding experience over ridges, rocks, logs, and other rough terrain.







## THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American Landmaster with the intention of our customers never needing to use a warranty, but we know things can happen. The **Easy Life Warranty** from American Landmaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. **As long as you care for your machine like you should we're going to cover it.** Except for tires, brake pads, batteries, damage, neglect. That's the limit. **Visit AmericanLandmaster.com to learn more.** 

,	POWER	AC motor, powered by a 48V DC Lithium-Ion Battery at 12K Watts with 600 amp Navitas controller (6.7 HP for long term driving, 16 HP for short term peak with 160 Amp Hour Battery)
/	SEATING CAPACITY	2-Person
/	SPEED	24MPH (Programmed at factory for LSV and Flip Seat compliance. Max speed of 30 available with Blue Tooth app.)
/	FUEL CONSUMPTION	N/A / / / /
	RANGE	Up to 45 miles (in MAX DISTANCE mode) with 105 AH battery @ 65 degrees) Up to 65 miles (in MAX DISTANCE mode with 160 AH battery @ 65 Degrees)**
/	STARTING	Keyed on/off
/	BATTERY	N/A
/	SPARK PLUG	N/A
	FUEL CAPACITY	N/A
/	ALTERNATOR	Converter / 30 amps
	TRANSMISSION	Direct drive
	TRANSAXLE	H-12 Schafer / DANA gearbox
	DIFFERENTIAL	Limited Slip Differential
/	DRIVE	2 wheel drive
	FRONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 8" travel
	REAR SUSPENSION	Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coil over shock with up to 8" of travel
	BRAKE SYSTEM	4 wheel disk, hydraulic brake.
/	TIRES	25" DOT On Road / Off Road Tire (8" front 10" back)
	DIMENSIONS	110" L x 58" W x 76" H
	WHEEL BASE	73.5"
	TURNING RADIUS	13' inside radius
	GVRW	HD-LROSS - 3,025 lbs.
	CURB WEIGHT	1350 lbs. with 105 AH battery
	BED MATERIALS	Structural foam "Poly Bed" with stake pockets
	BED DIMENSIONS	35.25" L x 41.5" W x 11" D
	BED CAPACITY	9.25 cu.ft. / 500 standard LROSS suspension / 700 HD LROSS suspsension lbs.
	TOWING CAPACITY	12000 lbs.
	TOTAL PAYLOAD	900 lbs.
	WARRANTY	2 year motor / all other 1 year limited, 5 year prorated Lithium battery
	ADDITIONAL FEATURES	On-board charger, 3pt lap/ shoulder belts for driver & passenger, 12V/18W LED headlights, 2" rear and front receiver hitch, welded/steel/frame, Single 12V auxiliary outlet for accessories, polyurethane powder paint. Complete weather-sealed wiring connections. Wide slection of additional accessories available along with three bed options. In-dash, hour meter standard. LED true state of charge meter for the 48 volt/system is standard. Low charge audible warning. Battery shut down switch. Electric accelerator pedal for better ergonomics and reliability.

Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.