

POWERFUL EFI 4X4, BUILT FOR WORK (shown with optional accessories)



4WD | 429cc



MADE IN THE U.S.A.





THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The Easy Life Warranty from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound/confusing? It isn't. Except for tires, brake pads, batteries, damage, neglect. That's the limit. Visit AmericanLandMaster.com to learn more.

/		
/	POWER	14hp 429cc Kohler EFI air-cooled OHV single cylinder
	SEATING CAPACITY	2-Person*
	SPEED	Up to 24 mph**
	FUEL CONSUMPTION	Up to 20 mpg* *
/	RANGE	Up to 100 miles**
/	STARTING	12V keyed ignition with recoil backup
/	BATTERY	12V / 360 cca utility class
	SPARK PLUG	NGK BPR6ES
	FUEL CAPACITY	5,0 gal
/	ALTERNATOR	25 amp
/	TRANSMISSION	CVT automatic
/	TRANSAXLE	Gear drive Schafer oil-filled transaxle
	DIFFERENTIAL	Cable Actuated Rear-Locking
	DRIVE	Switch engaged on demand, 4 wheel drive
	FRONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 7" travel
	REAR SUSPENSION	Independent trailing arm, with radius rod, adjustable camber & tow, dual-rate coil over shock with up to 8" of travel
	BRAKE SYSTEM	4 wheel disc, hydraulic brake
	TIRES	25 x 8 - 12 (front) 25 x 10 - 12 (rear)
	DIMENSIONS	95" L x 50" W x 76" H
	WHEEL BASE	73"
	TURNING RADIUS	7.5' inside radius
	GVRW	L-ROSS - 2,100 lbs. / HD L-ROSS - 2,200 lbs.
	CURB WEIGHT	1,200 lbs.
	BED MATERIALS	Structural foam "Poly Bed" with stake pockets
	BED DIMENSIONS	35.25" L x 41.5" W x 11" D
	BED CAPACITY	Poly - 9 cu.ft. / Steel - 11 cu.ft. / L-ROSS - 500 lbs. / HD L-ROSS - 600 lbs.
	TOWING CAPACITY	1,500 lbs.
	TOTAL PAYLOAD	L-ROSS - 900 lbs. / HD L-ROSS - 1,000 lbs.
	WARRANTY	3 year engine / All other 1 year limited
	ADDITIONAL FEATURES	3pt lap/shoulder belts for driver and passenger, 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2/ front and rear receiver hitch, poly dump bed standard, weather sealed contoured bench seating, welded steel frame. Complete weather-sealed wiring connections. Wide selection of additional accessories available along with three bed options. Fuel gauge located under seat. In-dash,

hour/volt meter standard.

^{*2} additional seats with optional seat bed.
** Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.