

# INDUSTRY'S HARDEST WORKING , SMOOTHEST RIDING UTV OF IT'S CLASS

*(shown with optional accessories)*



**4WD • POWER STEERING (EPS) • VANGUARD 627CC**



**MADE IN USA**

\*Price above does not include setup fees, destination charges, installation charges or any other fees charged at the dealership.



## THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The **Easy Life Warranty** from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. **As long as you care for your machine like you should, don't wreck it, or crush it, or let it be attacked by unruly farm animals, we're going to cover it.** Except for tires, brake pads, batteries, damage, neglect. That's the limit. **Visit [AmericanLandMaster.com](http://AmericanLandMaster.com) to learn more.**

POWER	23hp   627cc Commercial-Grade, V-Twin OHV-Technology, EFI Vanguard 4-stroke Gas Engine. Superior balance, low vibration, lower emissions, improved valve life, better fuel economy and higher HP/Weight
SEATING CAPACITY	2-Person*
SPEED	35mph +
FUEL CONSUMPTION	Up to 28 mpg**
RANGE	Up to 100 miles**
STARTING	12V keyed ignition - remote jump start terminals
BATTERY	12V / 315 cca utility class
SPARK PLUG	NGK C7HSA
FUEL CAPACITY	5.0 gal
ALTERNATOR	25 amp
TRANSMISSION	CVT automatic
TRANSAXLE	Gear drive Schafer/DANA oil-filled transaxle
DIFFERENTIAL	Cable Actuated Rear-Locking
DRIVE	Switch engaged on demand, 4 wheel drive
FRONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 8" travel
REAR SUSPENSION	Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coil over shock with up to 8" of travel
BRAKE SYSTEM	4 wheel disc, hydraulic brake
TIRES	25 x 8 - 12 (front) 25 x 10 - 12 (rear)
DIMENSIONS	110" L x 58" W x 76" H (110" with poly bed)
WHEEL BASE	73"
TURNING RADIUS	12' inside radius
GVRW	L-ROSS - 2,100 lbs. / HD-LROSS - 2,300 lbs.
CURB WEIGHT	1,200 lbs.
BED MATERIALS	Structural foam "Poly Bed" with stake pockets
BED DIMENSIONS	35.25" L x 41.5" W x 11" D
BED CAPACITY	Poly - 9 cu.ft. / Steel - 11 cu.ft. / L-ROSS - 500 lbs. / HD-LROSS - 700 lbs.
TOWING CAPACITY	1,500 lbs.
TOTAL PAYLOAD	L-ROSS - 900 lbs. / HD-LROSS - 1,100 lbs.
WARRANTY	3 year engine / All other 1 year limited
ADDITIONAL FEATURES	3pt lap/shoulder DOT certified belts for driver and passenger with driver indicator light, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" front and rear receiver hitch, dump bed, bench seating, welded steel frame. Complete weather-sealed wiring connections. Wide selection of additional accessories available along with three bed options. Fuel gauge located underside of bed. In-dash, hour/volt meter standard

\* 2 additional seats with optional seat bed.

\*\* Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.