## **OUR BIGGEST, BADDEST WORKHORSE**

**EXTRA PAYLOAD / EXTRA TORQUE** 

(shown with optional accessories)



4WD | 694cc



MADE IN THE U.S.A.



## L7xl PRO



WARRANTY

## THE BEST COMBINATION OF DURATION AND COVERAGE IN THE INDUSTRY

We build UTVs at American LandMaster with the intention of our customers never needing to use a warranty, but we know things can happen. The **Easy Life Warranty** from American LandMaster is a 12-month bumper-to-bumper limited warranty. Does limited sound confusing? It isn't. **As long as you care for your machine like you should, don't wreck it, or crush it, or let it be attacked by unruly farm animals, we're going to cover it. Except for tires, brake pads, batteries, damage, neglect. That's the limit. <b>Visit AmericanLandmaster.com to learn more.** 

	the limit. Visit AmericanLandmaster.com to learn more.
POWER	21hp   694cc LandMAXX EFI Commercial Power Engine by Kohler Command Pro® ECH650 rated at 21hp 4-stroke OHV V-twin with oil pressure warning light. Remote Air Cleaner
SEATING CAPACITY	2-Person
SPEED	Up to 24 mph**
FUEL CONSUMPTION	Up to 28 mpg**
RANGE	Up to 100 miles**
STARTING	12V keyed ignition - remote jump start terminals
BATTERY	12V / 315 cca utility class
SPARK PLUG	NGK C7HSA
FUEL CAPACITY	5.0 gal
ALTERNATOR	25 amp
TRANSMISSION	CVT automatic
TRANSAXLE	Gear drive Schafer/DANA oil-filled transaxle
DIFFERENTIAL	Cable Actuated Rear-Locking
DRIVE	Switch engaged on demand, 4 wheel drive
FRONT SUSPENSION	Double A-arms, adjustable coil over shock with up to 8" travel
REAR SUSPENSION	Independent trailing arm, with radius rod, adjustable camber & tow control, dual-rate coil over shock with up to 8" of travel
BRAKE SYSTEM	4 wheel disc, hydraulic brake
TIRES	25 x 10 - 12 (front) 25 x 10 - 12 (rear)
DIMENSIONS	145" L x 58" W x 76" H
WHEEL BASE	105"
TURNING RADIUS	16' inside radius
GVRW	HD-LROSS - 3,025 lbs.
CURB WEIGHT	1,625 lbs.
BED MATERIALS	XL Convertible Steel Bed / Flat Bed - with electric dump
BED DIMENSIONS	14.25"h x 50.25" w x 70" L (inside bed dimensions)
BED CAPACITY	Steel - 21 cu.ft. / HD-LROSS - 1000 lbs.
TOWING CAPACITY	1,750 lbs.
TOTAL PAYLOAD	HD-LROSS - 1,400 lbs.

ADDITIONAL FEATURES

Outlets for accessories, 12/18W LED neadignts, polyuretriane powder paint, 2 front and rear receiver nitch, poly dump is standard, bench seating, welded steel frame, Complete weather-sealed wiring connections. Wide selection of additional accessories available along with three bed options. In-dash, hour/volt meter standard

\*\* Estimates. Actual top speeds, fuel consumptions and vehicle ranges may vary due to driving conditions, terrain, climate and other extenuating circumstances.

3pt lap/shoulder DOT certified belts for driver and passenger with driver indicator light, Heavy Duty Bumper, twin 12V auxiliary outlets for accessories, 12V/18W LED headlights, polyurethane powder paint, 2" front and rear receiver hitch, poly dump bed

3 year engine / All other 1 year limited