# **S9056RT-HC/S9070RT-HC** ULTRA HIGH CAPACITY ROUGH TERRAIN SCISSOR LIFTS



- Ultra high capacity, large deck rough terrain scissor lifts
- Excellent rough terrain performance
- Heavy duty design
- Dual powered extension decks
- Ideal for construction applications



### **ULTRA HIGH CAPACITY ROUGH TERRAIN SCISSOR LIFTS**

DIMENSIONS	S9056RT-HC*	S9070RT-HC*	
Max. working height	62 ft	76 ft	
Max. platform height ( <b>A</b> )	56 ft	70 ft	
Platform size (stowed)	16 ft x 7 ft 6 in		
Platform size (dual decks extended)	25 ft x 7 ft 6 in		
Extension deck length	4 ft 6 in	4 ft 6 in	
Overall width ( <b>B</b> )	7 ft 6 in	7 ft 6 in	
Overall length ( <b>C</b> )	16 ft	16 ft	
Stowed height ( <b>D</b> )	10 ft 2 in	11 ft 3 in	
Min. height (guardrails folded)	7 ft	8 ft 5 in	
Ground clearance	14 in	14 in	

PERFORMANCE			
Platform capacity (SWL)	2,500 lbs	2,000 lbs	
Max. drive height	31 ft	31 ft	
Max. wind speed	28 mph	28 mph	
Max. drive speed (stowed)	4.2 mph	4.2 mph	
Max. drive speed (elevated)	0.6 mph	0.6 mph	
Raise/lower time	55/35 sec	70/40 sec	
Gradeability	50%	50%	
Max. stabilizer levelling, front to rear	6°	6°	
Max. stabilizer levelling, side to side	14°	14º	
Inside turning radius	8 ft	8 ft	
Outside turning radius	18 ft 6 in	18 ft 6 in	
Tires	13 x 36 foam filled		
Controls	proportional joystick		
Drive system	4 wheel drive		


#### POWER

Power source


Kubota diesel

WEIGHT		
Weight	20,000 lbs	25,500 lbs

#### **TURNING RADIUS**



# **S9056RT-HC/ S9070RT-HC**



### **STANDARD FEATURES**

- 4 wheel drive •
- 4 hydraulic stabilizers with automatic levelling
- Dual powered extension decks
- Proportional controls
- Foam filled tires
- Power line to platform
- Drive motion alarm •
- Descent alarm
- Locking articulating axle •
- Fold-down guardrails
- Manual lowering valve •
- Flashing amber light ٠
- Dual lanyard attachment points
- Hour meter & on-board diagnostics display •
- 2 year parts & labor, 5 year structural warranty •
- ANSI compliant

#### **OPTIONS**

- Special paint colors
- Nylon spreader pads (set of 4)
- Environmental hydraulic oil
- Dual fuel
- LPG power
- Cold weather package (block heater + battery warm up) •
- Hydraulic 2kW generator
- Hydraulic 12kW generator •



P.O. Box 1160 St.Joseph, MO 64502-1160, USA Tel: 1 (785) 989-3000 Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070 Email: sales.usa@snorkellifts.com

ANSI Specification ©Snorkel 2020

Specifications subject to change without notice. Photos and diagrams in this brochure are for promotional purposes only. Refer to appropriate Snorkel operators manual for detailed instructions on the proper use and maintenance \* Preliminary specifications - confirm at time of ordering.

.com