



# VERTEX® S-SERIES

DURABLE. SIGNATURE QUALITY OF CUT. COMMERCIAL PERFORMANCE.

## FEATURES

### UltraCut™ Series 4 Deck

Side Discharge: 48 | 52 | 60

### Commercial-Grade Engine

Kawasaki® or Kohler®

### Operator Comfort

Full-length operator pad

### Serviceability and Accessibility

Patent pending removable, toolless operator pad for easy removal



### DESIGN SIMPLICITY

Operating a Vertex mower is easy, thanks to the simple, ergonomic design. Key, choke, throttle, height of cut adjustment... they're all right there. Hop on, and you're ready to go.



### QUALITY OF CUT

Vertex S-Series stand-ons are built to consistently deliver the legendary quality of cut all Exmark mowers are famous for.

## TOP ACCESSORIES

- 3-Bushel Bagger
- Equipment Cover
- LED Light Kit
- Micro-Mulch System
- Operator Control Discharge (Hand)
- Operator Control Discharge (Foot)
- Trash Container
- Turf Stripping Kit

Accessories may not fit each mower model. Please visit [exmark.com](http://exmark.com) or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

[exmark.com](http://exmark.com)

# VERTEX S-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
VXS730GKA48400	FX730V Kawasaki V-Twin	48"	UltraCut Series 4	925 lbs.	60.1" x 49.2" x 65.3"
VXS730GKA52400	FX730V Kawasaki V-Twin	52"	UltraCut Series 4	936 lbs.	64.8" x 49.2" x 65.3"
VXS740EKC52400	ECV740 Kohler EFI	52"	UltraCut Series 4	987 lbs.	64.8" x 49.2" x 65.3"
VXS730GKA60400	FX730 Kawasaki V-Twin	60"	UltraCut Series 4	978 lbs.	72.9" x 49.2" x 68.2"
VXS740EKC60400	ECV740 Kohler EFI	60"	UltraCut Series 4	1026 lbs.	72.9" x 49.2" x 68.2"



Side Discharge



Side Discharge

## POWER COMPONENTS

**Engine** – FX730V Kawasaki V-Twin and ECV740 Kohler engines. All engines governed to 3,600 rpm.

**Air Filter** – Heavy-duty canister air filtration system.

**Drive System** – Two Hydro-Gear 12cc pumps powering two Parker 14.5 cubic inch motors.

**Hydro Fluid** – Exmark Premium Hydro Oil.

**Speed** – Infinitely variable speed selection 0–8.5 mph (13.7 kmph) forward, 0–5.5 mph (8 kmph) reverse.

**PTO Engagement** – Warner 200 ft-lb clutch.

**Fuel Capacity** – 8-gallon (30.3-L), single fuel tank on left hand side.

**Drive-Wheel Release** – Allows unit movement without engine running.

**Safety Package** – Operator Presence Controls (OPC) with safety interlock system indicators.

**Deck Lift** – Single-point height-of-cut with mechanical lift-assist spring.

## DECK

**Style** – Full-floating UltraCut™ Series 4 on 48", 52" and 60" units. Side-discharge standard with molded discharge chute and option to bag or mulch.

**Deck Construction** – 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt.

**Widths Available** – 48" (122 cm), 52" (132 cm) and 60" (152 cm).

**Cutting Height** – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.25" (0.64 cm) increments adjustable from operator's platform.

**Blade Spindles** – No maintenance, sealed and nongreasable spindles; 7.75" diameter cutter housing with 1.75" diameter splined blade driver 1.0"-diameter spindle shaft.

**Blade-Tip Speed** – Approximately 18,500 fpm.

## EQUIPMENT

**Tractor Frame** – Welded, heavy-duty 1.5" x 2.5" tubular steel.

**Suspension Platform** – Adjustable operator platform suspension.

**Steering and Motion Control** – Twin levers with center fixed reference bar for ease of control forward and reverse.

**Casters** – 0.50" thick caster yoke arms with tapered roller bearings.

**Front Caster Tires** – 13 x 5.0-6, smooth-tread, semi-pneumatic tires with tapered roller bearings.

**Drive Tires** – 20 x 10.0-8 Carlisle Turf Master.

**Turning Radius** – True zero-turn.

**Parking Brake** – Lever-actuated bar brake.

**Electrical** – 12-volt battery with 15-amp alternator on Kawasaki units. 12-volt battery with 20-amp alternator on Kohler units.

**Standard Features** – Enhanced engine hour meter.

## ACCESSORIES & OPTIONS

3-Bushel Bagger, Equipment Cover, Hydro Maintenance Kit, Jack and Jack Mount Receiver, LED Light Kit, Micro-Mulch System, Operator Controlled Discharge (Hand or Foot), Strobe Light Kit, Trash Container and Turf Stripping Kit.

*Accessories may not fit each model. Please visit [exmark.com](http://exmark.com) or check with your dealer on accessory fit-up for each model.*

## WARRANTY

Limited Warranty: 4-Year or 1,250 Hours (with No Hour Limit First 2 Years), 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • [exmark.com](http://exmark.com)

<sup>1</sup> Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut ÷ 99 = acres per hour | 80% efficiency: MPH x width of cut ÷ 124 = acres per hour.

<sup>2</sup> For complete details, visit [exmark.com](http://exmark.com) or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Vertex® are registered trademarks of Exmark Mfg. Co., Inc. ©2022 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2022. Rev 1.