



COMMERCIAL 21 X-SERIES

PRODUCTIVITY. COMMERCIAL DURABILITY. EASE OF USE.

FEATURES


5-inch Deep Cast Aluminum Cutting Deck
2-in-1: Bag and Mulch

Commercial-Grade Engines
Honda® or Kawasaki®

Patented Front Height Adjustment System
Eliminates pivot-style adjusters, now with improved grips for added comfort on height-of-cut adjustments

Infinite Speed Control
Multi-zone transmission provides infinite speed control from zero to 4.2 mph

Multiple Blade Options
The option of five blade choices gives you the flexibility to customize for your unique cutting conditions



ACCESSORIES

None Available

EASE OF USE

The Commercial 21 has simple, straightforward controls and a lightweight, durable cast aluminum cutting deck, which reduces weight and eases maneuverability.

THE EXMARK® SIGNATURE CUT

The true test of a mower is the cut quality it delivers. The Commercial 21 is engineered to consistently deliver an unmatched quality of cut, whether mulching or bagging. A variety of optional blades let you further optimize performance for your specific cutting conditions.

The commercial mowers more landscape pros trust.

exmark.com

COMMERCIAL 21 X-SERIES

MODEL	ENGINE	SIZE	CONTROLS	WEIGHT	DIMENSIONS (W X H X L)
ECX180GKA21000	FJ180V Kawasaki KAI	21"	Self-Propelled Zone	123 lbs.	22" x 38.0" ¹ x 62.0"
ECX160GHN21000	GXV160 Honda	21"	Self-Propelled Zone	112 lbs.	22" x 38.0" ¹ x 62.0"
ECX180GKA210BC	FJ180V Kawasaki KAI	21"	Self-Propelled BBC	123 lbs.	22" x 38.0" ¹ x 62.0"

Varies with 0.5" cutting selections.



POWER COMPONENTS

Engine – FJ180V Kawasaki KAI engine governed to 3,300 rpm; GXV160 Honda engine governed to 3,300 rpm.

Air Filter – Dual element air cleaner.

Drive System – Self-propelled, rear-wheel gear-driven.

Transmission – Infinitely variable speed selection, dual wheel drive.

Fuel Capacity – 1 gallon (3.8-L) fuel tank.

Speed – 0.0 mph to 4.2 mph (6.6 kmph) forward.

Speed Control - Finger-tip control.

DECK

Style – Fixed-deck, rear-discharge bagger and mulch plug standard.

Widths Available – 21" (53.3 cm).

Cutting Height – 1.0" (2.5 cm) to 4.5" (11.4 cm) in 0.5" (1.3 cm) increments.

Blade – 1 blade at 20.5".

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Engine Deck – 5-inch-deep, 1/4-inch-thick die-cast aluminum.

Drive Tires – 9 x 2.4, semi-pneumatic.

Safety Package – Zone start/Blade Brake Clutch (BBC).

Bag Capacity – 2.5 bushels (20 gallons).

ACCESSORIES & OPTIONS

No accessories available.

WARRANTY

1-Year Commercial/Consumer, 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut = 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® is a registered trademark of Exmark Mfg. Co., Inc.

©2024 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2024. Rev 1.