



VERTEX® X-SERIES

DURABLE. SIGNATURE QUALITY OF CUT. COMMERCIAL PERFORMANCE.

FEATURES

UltraCut™ Series 6 Deck

Side Discharge: 52 | 60 | 72

Commercial-Grade Engine


Kawasaki® FX1000V

Operator Comfort

Full-length operator pad

Serviceability and Accessibility

Patent pending removable, tool-less operator pad for easy removal



DESIGN SIMPLICITY

Operating a Vertex mower is easy, thanks to the simple, ergonomic design. Key, choke, throttle, height of cut adjustment... they're all right there. Hop on, and you're ready to go.



QUALITY OF CUT

Vertex X-Series stand-ons are built to consistently deliver the legendary quality of cut all Exmark mowers are famous for.

TOP ACCESSORIES

- Equipment Cover
- LED Light Kit
- Micro-Mulch System
- Operator Control Discharge (Hand or Foot)
- Trash Container
- Turf Striping Kit
- UltraVac Collection System, 2-Bag

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

exmark.com

VERTEX X-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X H X L)
VXX999EKA52600	FX1000V EFI ETC Kawasaki V-Twin	52"	UltraCut Series 6	1,250 lbs.	64.8" x 48.8" x 70.5"
VXX999GKA52600	FX1000V Kawasaki V-Twin	52"	UltraCut Series 6	1,250 lbs.	64.8" x 48.8" x 70.5"
VXX999EKA60600	FX1000V EFI ETC Kawasaki V-Twin	60"	UltraCut Series 6	1,310 lbs.	72.9" x 48.8" x 73.4"
VXX999GKA60600	FX1000V Kawasaki V-Twin	60"	UltraCut Series 6	1,310 lbs.	72.9" x 48.8" x 73.4"
VXX999EKA72600	FX1000V EFI ETC Kawasaki V-Twin	72"	UltraCut Series 6	1,400 lbs.	84.8" x 48.8" x 77.1"
VXX999GKA72600	FX1000V Kawasaki V-Twin	72"	UltraCut Series 6	1,400 lbs.	84.8" x 48.8" x 77.1"



Side Discharge



Side Discharge

POWER COMPONENTS

Engine – Carbureted or EFI ETC FX1000V Kawasaki V-Twin. All engines governed to 3,600 rpm.

Air Filter – Heavy-duty canister air filtration system

Drive System – Two Hydro-Gear 16cc pumps powering two Hydro-Gear 17.8 cubic inch motors.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable speed selection 0–12.0 mph (19.3 kmph) forward, 0–5.0 mph (8.0 kmph) reverse.

PTO Engagement – Warner 250 ft-lb clutch.

Fuel Capacity – 14-gallon (53.0-L), dual fuel tanks on left and right sides.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) with safety interlock system indicators.

Deck Lift – Single-point height-of-cut with mechanical lift-assist spring.

DECK

Style – Full-floating UltraCut™ Series 6 on 52," 60" and 72" units. Side-discharge standard with molded discharge chute and option to mulch or mulch.

Deck Construction – 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt

Widths Available – 52" (132 cm), 60" (153 cm) and 72" (183 cm).

Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.25" (0.64 cm) increments adjustable from operator's platform.

Blade Spindles – No maintenance, sealed and nongreasable spindles; 7.75" diameter cutter housing with 1.0"-diameter spindle shaft, double row bearings, top and bottom and 1.75" diameter splined blade driver

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Tractor Frame – Welded, heavy-duty 1.5" x 3" tubular steel.

Suspension Platform – Adjustable operator platform suspension.

Steering and Motion Control – Twin levers with center fixed reference bar for ease of control forward and reverse.

Casters – 0.50" thick caster yoke arms with tapered roller bearings.

Front Caster Tires – 15 x 6.0-6, smooth-tread, semi-pneumatic tires with tapered roller bearings.

Drive Tires – 24 x 9-10 on 52" unit. 24 x 9-12 on 60" and 72" unit.

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated internal motor brake.

Electrical – 12-volt battery with 30-amp alternator.

Standard Features – Enhanced engine hour meter.

ACCESSORIES & OPTIONS

3-Bushel Bagger, Equipment Cover, Hydro Maintenance Kit, Jack, LED Light Kit, Micro-Mulch System, Operator Controlled Discharge (Hand or Foot), Strobe Light Kit, Tractus Tires, Trash Container, Turf Striper and UltraVac 2-Bag Collection System.

Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

WARRANTY

Limited Warranty: 5-Year or 1,500 Hours (with No Hour Limit First 2 Years), 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut = 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Vertex® are registered trademarks of Exmark Mfg. Co., Inc. ©2024 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2024. Rev 1.