



# 96-INCH LAZER Z® X-SERIES

UNMATCHED PERFORMANCE. LEGENDARY DURABILITY.

## FEATURES

### UltraCut™ Deck Technology

Rear Discharge with Flex Wings: 96

### Commercial-Grade Engines

Kohler®

### Frame Durability

Features a rear cast belly and fully reinforced tubular frame that's formed and welded from 7-gauge, high-strength steel.

### Hydro-Drive System

Eliminated hoses and added tougher bearings, an improved cooling system and increased oil capacity.



### ENGINE PROTECTION

A reduction of operating temperatures is provided by an external oil cooler and an engine hood designed to screen intake air coming into the engine. This provides an ample supply of cool, clean air, while reducing the potential for debris build-up around cooling fins.



### REAR DISCHARGE WITH FLEX WINGS

The wings flex 20-degrees up and 15-degrees down. For easy transport and trailering, the wings fold-up to 72.5-inches wide at a 3-inch cut height.

## TOP ACCESSORIES

- Black Side Bumper
- White Non-Marking Side Bumper
- Jack Mount Receiver
- LED Light
- Rear Discharge Baffle
- Sun Shade

The commercial mowers more landscape pros trust.

[exmark.com](http://exmark.com)

# LAZER Z X-SERIES

MODEL	ENGINE	SIZE	DECK	WEIGHT	DIMENSIONS (W X L X H)
LZX980EKC96RW0	ECV980 Kohler EFI RED Equipped	96"	UltraCut Rear Discharge w/ flex wings	2200 lbs.	101.3" x 95.8" x 70.5"



## POWER COMPONENTS

**Engine** – ECV980 Kohler Command EFI engine with electronic throttle body. Governed to 3,650 rpm.

**Air Filter** – Heavy-duty canister air filtration system drawing through pre-screen.

**Drive System** – Two Exmark® exclusive Parker unitized pump and wheel motor systems with no hoses, integrated cooling fans, 1.7-quart integrated reservoir, spin-on filter and heavy-duty components.

16cc pumps and 18.9 cubic inch motors.

**Hydro Fluid** – Exmark Premium Hydro Oil.

**Speed** – Infinitely variable speed selection from 0–10.5 mph (16.9 kmph) forward, 0–6.0 mph (9.7 kmph) reverse.

**PTO Engagement** – MagStop Electromagnetic 250-ft-lbs clutch with spot brake.

**Fuel Capacity** – High-capacity, 12-gallon (45.4-L), single fuel tank with single fill location.

**Drive-Wheel Release** – Allows unit movement without engine running.

**Safety Package** – Operator Presence Controls (OPC) and drive system interlock, with safety interlock system indicators.

**Rollover Protection System (ROPS)** – 2-post foldable ROPS standard with seat belt and latch.

**Quick Deck Lift** – Standard; electric over hydraulic push button control.

## DECK

**Style** – Full-floating UltraCut Rear Discharge deck. Finish cut baffles installed.

**Deck Construction** – 7-gauge high strength alloy top that is formed and welded, with 7-gauge high strength alloy side skirt

**Widths Available** – 96" (244 cm).

**Cutting Height** – 1.0" (2.5 cm) to 5.5" (11.8 cm) in 0.25" (0.64 cm) increments adjustable from operator's seat.

**Blade Spindles** – No maintenance, sealed and non-greasable spindles; 7.75"-diameter cutter housing with 25mm (.98") diameter spindle shaft, double row bearings, top and bottom, and splined blade driver.

**Blade-Tip Speed** – Approximately 18,500 fpm.

## EQUIPMENT

**Tractor Frame** – Unibody, welded, heavy-duty 1.5" x 3" tubular steel.

**Steering and Motion Control** – Hydraulically dampened twin levers, adjust fore and aft. Adjustable dampeners (3 positions) to customize drive responsiveness. Also adjustable to 2 height positions.

**Casters** – .50" thick caster yoke arm.

**Front Caster Tires** – 13 x 6.5-6 smooth tread, semi-pneumatic.

**Drive Tires** – 24 x 12.0-12, 4-ply Turf Master.

**Turning Radius** – True zero-turn.

**Parking Brake** – Lever-actuated disc brake.

**Seat Comfort** – Deluxe, two-tone, bolstered suspension seat with Elastomeric Vibration Control material. Mounted on innovative Seat Isolation System that provides operator isolation in all three planes of motion as well as fore-aft slide and seat flip-up.

**Onboard Intelligence** – Equipped with Next-Generation RED technology.

**Electrical** – 12-volt battery with 40-amp alternator.

**Standard Features** – Engine hour meter and cup holder

## ACCESSORIES & OPTIONS

12-Volt Power Adapter, Extended Drive Lever Kit, Floor Mat, Hydro Maintenance Kit, Jack, Jack Mount Receiver, LED Light, Rear Discharge Baffle Kit, Slope Sensor, Sun Shade, White Non-Marking Side Bumper and Black Side Bumper.

*Accessories may not fit each model. Please visit [exmark.com](http://exmark.com) or check with your dealer on accessory fit-up for each model.*

## WARRANTY

Limited Warranty: 5-Year or 1,500 Hours (with No Hour Limit First 2 Years), 3 Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • [exmark.com](http://exmark.com)

<sup>1</sup> Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut =124 = acres per hour.

<sup>2</sup> For complete details, visit [exmark.com](http://exmark.com) or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Lazer Z® are registered trademarks of Exmark Mfg. Co., Inc. ©2024 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2024. Rev 1.