



VERTEX® S-SERIES

DURABLE. SIGNATURE QUALITY OF CUT. COMMERCIAL PERFORMANCE.

FEATURES

UltraCut™ Series 4 Deck
Side Discharge: 48 | 52 | 60

Commercial-Grade Engine
Kawasaki® or Kohler®

Operator Comfort
Full-length operator pad

Serviceability and Accessibility
Patent pending removable, tool-less operator pad for easy removal



DESIGN SIMPLICITY

Operating a Vertex mower is easy, thanks to the simple, ergonomic design. Key, choke, throttle, height of cut adjustment... they're all right there. Hop on, and you're ready to go.



QUALITY OF CUT

Vertex S-Series stand-ons are built to consistently deliver the legendary quality of cut all Exmark mowers are famous for.

TOP ACCESSORIES

- 3-Bushel Bagger
- Equipment Cover
- LED Light
- Micro-Mulch System
- Operator Control Discharge (Hand)
- Operator Control Discharge (Foot)
- Trash Container
- Turf Stripping Kit

Accessories may not fit each mower model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

The commercial mowers more landscape pros trust.

exmark.com

VERTEX S-SERIES

| MODEL | ENGINE | SIZE | DECK | WEIGHT | DIMENSIONS (W X H X L) |
|-------------------------------|------------------------|------|-------------------|-----------|------------------------|
| VXS740EKC48400 | ECV740 Kohler EFI | 48" | UltraCut Series 4 | 925 lbs. | 60.1" x 49.2" x 65.3" |
| VXS730GKA48400 | FX730V Kawasaki V-Twin | 48" | UltraCut Series 4 | 925 lbs. | 60.1" x 49.2" x 65.3" |
| VXS750AKC48400 <i>CA Only</i> | EZT750 Kohler EFI | 48" | UltraCut Series 4 | 925 lbs. | 60.1" x 49.2" x 65.3" |
| VXS730GKA52400 | FX730V Kawasaki V-Twin | 52" | UltraCut Series 4 | 936 lbs. | 64.8" x 49.2" x 65.3" |
| VXS740EKC52400 | ECV740 Kohler EFI | 52" | UltraCut Series 4 | 987 lbs. | 64.8" x 49.2" x 65.3" |
| VXS730GKA60400 | FX730 Kawasaki V-Twin | 60" | UltraCut Series 4 | 978 lbs. | 72.9" x 49.2" x 68.2" |
| VXS740EKC60400 | ECV740 Kohler EFI | 60" | UltraCut Series 4 | 1026 lbs. | 72.9" x 49.2" x 68.2" |



Side Discharge



Side Discharge

POWER COMPONENTS

Engine – FX730V Kawasaki V-Twin and ECV740 Kohler engines. All engines governed to 3,600 rpm.

Air Filter – Heavy-duty canister air filtration system.

Drive System – Two Hydro-Gear 12cc pumps powering two Parker 14.5 cubic inch motors.

Hydro Fluid – Exmark Premium Hydro Oil.

Speed – Infinitely variable speed selection 0–8.5 mph (13.7 kmph) forward, 0–5.5 mph (8 kmph) reverse.

PTO Engagement – Warner 200 ft-lb clutch.

Fuel Capacity – 8-gallon (30.3-L), single fuel tank on left hand side.

Drive-Wheel Release – Allows unit movement without engine running.

Safety Package – Operator Presence Controls (OPC) with safety interlock system indicators.

Deck Lift – Single-point height-of-cut with mechanical lift-assist spring.

DECK

Style – Full-floating UltraCut™ Series 4 on 48", 52" and 60" units. Side-discharge standard with molded discharge chute and option to bag or mulch.

Deck Construction – 10-gauge top that is formed and continuously seam welded, 7-gauge side skirt.

Widths Available – 48" (122 cm), 52" (132 cm) and 60" (152 cm).

Cutting Height – 1.5" (3.8 cm) to 5.0" (12.7 cm) in 0.25" (0.64 cm) increments adjustable from operator's platform.

Blade Spindles – No maintenance, sealed and nongreasable spindles; 7.75" diameter cutter housing with 1.75" diameter splined blade driver 1.0"-diameter spindle shaft.

Blade-Tip Speed – Approximately 18,500 fpm.

EQUIPMENT

Tractor Frame – Welded, heavy-duty 1.5" x 2.5" tubular steel.

Suspension Platform – Adjustable operator platform suspension.

Steering and Motion Control – Twin levers with center fixed reference bar for ease of control forward and reverse.

Casters – 0.50" thick caster yoke arms with tapered roller bearings.

Front Caster Tires – 13 x 5.0-6, smooth-tread, semi-pneumatic tires with tapered roller bearings.

Drive Tires – 20 x 10.0-8 Carlisle Turf Master.

Turning Radius – True zero-turn.

Parking Brake – Lever-actuated bar brake.

Electrical – 12-volt battery with 15-amp alternator on Kawasaki units. 12-volt battery with 20-amp alternator on Kohler units.

Standard Features – Enhanced engine hour meter.

ACCESSORIES & OPTIONS

3-Bushel Bagger, Equipment Cover, Hydro Maintenance Kit, Jack and Jack Mount Receiver, LED Light, Micro-Mulch System, Operator Controlled Discharge (Hand or Foot), Strobe Light Kit, Trash Container and Turf Stripper.

Accessories may not fit each model. Please visit exmark.com or check with your dealer on accessory fit-up for each model.

WARRANTY

Limited Warranty: 4-Year or 1,250 Hours (with No Hour Limit First 2 Years), 3-Year Engine



EXMARK MANUFACTURING COMPANY INC. • 415 INDUSTRIAL ROW • BEATRICE, NE 68310 • Call 402.223.6300 • exmark.com

¹ Many manufacturers use 100% efficiency ratings for sale purposes. Exmark believes an 80% efficiency rating is more representative of actual mowing conditions, as it allows for turns and overlapping. Formulas for calculating acres per hour: 100% efficiency: MPH x width of cut = 99 = acres per hour | 80% efficiency: MPH x width of cut = 124 = acres per hour.

² For complete details, visit exmark.com or your local dealer.

Products depicted in this literature are for demonstration purposes only. Actual products offered for sale may vary in use, design, required attachments and safety features. We reserve the right to improve our products and make changes in specifications, designs and standard equipment without notice and without incurring obligations. See your dealer for details on all of our warranties. Exmark® and Vertex® are registered trademarks of Exmark Mfg. Co., Inc. ©2024 Exmark Manufacturing Company, Inc. All Rights Reserved. Printed in the U.S.A. 2024. Rev 1.